

## UP---.0702

- Very high wear-resistance
- Fine grained structure
- Easy to weld
- Special machining on request
- Max length in one piece 12 m

Versions of delivery:

Sandblasted (standard) UP---.0702

Sandblasted + fine straightened style UP---.0703

Ordering example: UP 070.0700-2800

U-Profile with inside measurement 70,8 mm, length 2800 mm

Dimensions in mm.

**Material:** 18MnNb 6 with plenty more load capacity by addition of Niob (Nb) and vanadium (V)


**Sizes Available:** 60; 70; 80; 90; 110; 120; 150; 180



## General Data

Designation	Weight (kg/m)
UP060.0702	10.50
UP070.0702	14.80
UP080.0702	20.90
UP090.0702	28.60
UP110.0702	36.00
UP120.0702	42.80
UP150.0702	52.30

## Dimensions



Designation	B	D	H	I	T
UP060.0702	36	7 ±0.5	86.5	62.5 +1	12 ±0.5
UP070.0702	40 ±0.8	7.7 ±0.5	103.2	70.8 ±0.5	16.2 ±0.5
UP080.0702	41 ±0.5	10.8 ±0.5	121.3	78.7 ±0.5	21.2 ±0.5
UP090.0702	53 ±0.5	12.7 ±0.5	135.4	89.4 ±0.5	23 ±0.5
UP110.0702	61.2 ±0.8	14 ±0.5	157.2	108.4 ±0.5	24.4 ±0.5
UP120.0702	66.2 ±0.8	16.2 ±0.5	175	123.8 ±0.5	25.6 ±0.5
UP150.0702	71.2 ±0.8	19.4 ±0.5	201.5	150.1 ±0.5	25.7 ±0.5